

PRODUCT DESCRIPTION

A professional, flexible, paintable glue, assembly and sealant based on MSP.

SCOPE

CONSTRUCTION SEALER 60 ® is a high quality product for both adhesives, assembly and sealing of virtually all materials and (even wet) undergrounds. Indoor and outdoor use without a border area pollution. Suitable for damp locations. Paintable with most types of acrylic latex and Alkyd.

Bonding: wall panels, glass, mirrors, many plastics (acrylic), (natural) stone, concrete, wood, and many metals.
Mounting: skirting boards, battens, window sills, thresholds and insulation.

Sealing: antifungal joints in bathrooms, kitchens, deckseams, repair of roofs, gutters and top seal in glazing.

PROCESSING

Editing substrate, the substrate must be clean, dust and grease are. Using PRIMER CS 60 ® is only necessary where extreme structural requirements are combined with very porous surfaces eg by bonding of cladding. Not recommended substrates: PE, PP and Teflon. Tools: syringe tube with hand or hand-airpistol. Adhesives and mounting: application in stripes or dots. Tamping and / or fix and let harden. Do not use below 5 ° C. Remove wet adhesive residue CLEANER CS 60 ®. Sealing: For optimum performance of the kit, the joint as deep as wide make at least 5 mm. Sealant with a wet finger or a wet spatula.

PROPERTIES

Moisture and frost resistance	: good.
Chemical resistance and salts.	: resistant to all weather, UV light, short action of dilute acids, alkalis
Overcoatability	: good.
Elasticity	: permanently elastic.

TECHNICAL DATA

Basic Material	: moisture hardening MSP Polymers
Color	: brown, gray, white, black. Other colors available on request.
Density	: 1480 kg/m ³
Skin	: approx 10 min.
Tack free time	: approx 60 min.
Hardness	: approx 60 grams shore A
Shrinkage	: none
By Harding	: approx 2 mm per 24 hours
Elongation	: 300%
Tensile strength	: about 2.2 N/mm ²
Temperature resistance	: from -40°C to 100°C

SHELF LIFE

CONSTRUCTION SEALER 60 ® is in a sealed container in a cool frost free place, at least 9 months shelf life after manufacturing.

PACKAGING

Cartridges of 290 ml syringe and sausages of 600 ml.

SAFETY

- Ensure adequate ventilation;
- Avoid prolonged skin contact and wash hands regularly;
- a MSDS is available on request.